



SPECIMEN LABEL

GUARANTEED ANALYSIS:

Calcium (Ca).....	25.0%
Calcium Carbonate* (CaCO ₃).....	63.0%
Magnesium Carbonate (MgCO ₃).....	0.5%
Calcium Carbonate Equivalent (CCE).....	63.0%
Calcium Oxide Equivalent (CaO).....	37.6%
Magnesium Oxide Equivalent (MgO).....	0.5%
Moisture Content (maximum).....	35.0%
Effective Neutralizing Value (ENV).....	63.0%
Effective Calcium Carbonate Equivalent (ECCE).....	63.0%

PARTICLE SIZE INFORMATION:

Percent of material passing:	
8 mesh screen.....	100.0%
10 mesh screen.....	100.0%
20 mesh screen.....	100.0%
40 mesh screen.....	100.0%
50 mesh screen.....	100.0%
60 mesh screen.....	100.0%
100 mesh screen.....	100.0%
200 mesh screen.....	100.0%
Moisture, Maximum.....	35.0%

*Derived from: Limestone

Relative Neutralizing Value: 63.0%

Density 14.1 lbs./gallon

Neutralizing Index Zone (4) 70-79 for Liquid.

NOTE: Calcium Carbonate Equivalent on Dry Basis is min. 99.0%.

Neutralizing Index Zone (2) 90-99 for Dry Basis.

DIRECTIONS AND APPLICATION:

SHAKE WELL BEFORE USING – Agitation is required when mixing. Suggested dilution rate for general use is 5-10 gallons of water per one (1) gallon of Calcis if applying with a pump/sprayer system. For more specifications on application methods and rate instructions: Contact BioSafe Systems with any questions or concerns regarding product applications.

HANDLING & DISPOSAL

Use adequate ventilation and respiratory protection. Avoid breathing fertilizer mists. Avoid eye and skin contact. Wash hands thoroughly after using product.

Disposal: Do not reuse container. Follow all local, State and Federal laws for proper disposal.

WARRANTY: BioSafe Systems LLC warrants that this product conforms to the description on the label and is reasonably fit for the purposes stated in the Directions for Use, subject to the inherent risks referred to above when used in accordance with directions under normal use conditions. This warranty does not extend to the use of the product contrary to label instructions, or under abnormal conditions or under conditions not reasonably foreseeable to or beyond the control of Seller or BIOSAFE SYSTEMS LLC, and Buyer and User assume the risk of any such use. TO THE EXTENT CONSISTENT WITH APPLICABLE LAW, BIOSAFE SYSTEMS LLC MAKES NO WARRANTIES OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE, NOR ANY OTHER EXPRESSED OR IMPLIED WARRANTY EXCEPT AS STATED ABOVE.

DANGER – PELIGRO

KEEP OUT OF REACH OF CHILDREN

DO NOT ALLOW TO FREEZE | SHAKE WELL BEFORE USING



HAZARD STATEMENTS: See Safety Data Sheet for safe handling information.

May cause cancer. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective clothing, eye protection, and face protection. If exposed or concerned: Get medical advice/attention. Store locked up. Dispose of contents/container to an approved waste disposal plant.

Florida and North Carolina note: This product as received requires 2,816 pounds to be equal to one ton of standard liming material.

LIQUID LIME POND SUPPLEMENT:

Calcis is a proprietary micronized calcitic limestone suspension specially formulated for pond applications that safely and effectively harnesses natural limestone to raise alkalinity and hardness, adjust and buffer pH, add essential nutrients for pond life, and clarify water.

Use within 30 days of purchase or agitate container periodically to keep material in solution.

Read the entire label before using Calcis. Use this product only according to label directions.

 **BioSafe Systems**

For additional information on Calcis® call us toll-free at 1-888-273-3088 or visit www.BioSafeSystems.com.

©2022 BioSafe Systems, LLC. Calcis® is a registered trademark of BioSafe Systems, LLC. Always read and follow label directions.

V3-081922 10.22